



## MT 71 S

studio microphone

with original M7 capsule

- condenser microphone
- cardioid
- large diaphragm capsule
- PVC diaphragm
- transistor pre-amplifier
- phantom powering P48

Delivery, Options and Accessories	Typ	Order-No.
Studio microphone, satin nickel	MT 71 S	211126
Windscreen, anthracite	W 76	202407
Popscreen, black	P 110	600097
Foam disk, spare part for P 110, black		600168
Popscreen, black	P 110.W	610189
Microphone holder, satin nickel	MH 93.1	202304
Elastic suspension, satin nickel	EH 93 P	202357
Elastic suspension incl. A93, satin nickel	EA 93	212311
Adaptor for elastic suspension EA 93, nickel matt	A 93	202354
Connection cable, 10 m, XLR, black	C 70.1	202212
Connection cable, 10 m, XLR, RFI-shielded, black	C 70.1 HF	202213
Microphone bar, 25 cm, for XY / ORTF, black anodised	KS 25	202398

# MT 71 S



Polar pattern	cardioid	
Acoustic operating principle	pressure gradient transducer	
Frequency range	20 Hz to 20.000 Hz	
Sensitivity at 1 kHz	13 mV/Pa $\pm$ 3 dB	
Switch position "reduced bass roll-off" at 90 Hz	-10 dB $\pm$ 1 dB	
Output impedance	150 $\Omega$	
Noise level	CCIR 468-4	22 dB
	DIN EN 60268-4	14 dB-A
Signal-to-noise ratio	CCIR weighted	72 dB
	A-weighted	80 dB
SPL for THD 0,5 %	134 dB	
with 10 dB preattenuation	144 dB	
Dynamic range	120 dB	
Current consumption	3 mA	
Output connector	XLR3M	
Weight	285 g	
Dimensions (L x $\varnothing$ )	217 mm x 42 capsule / 21 mm preamplifier	

